

Secondary Legislation



MARITIME TRANSPORT (BULWARKS, RAILS, AND GUARDS) INSTRUMENT

MTI-404.181-1

This maritime transport instrument is—

- (a) made by the Director of Maritime New Zealand under section 452B of the Maritime Transport Act 1994 (the Act), after being satisfied that appropriate consultation has been carried out in accordance with section 452C of the Act; and
- (b) referred to in rule 404.181 of Part 404: Design, Construction, and Equipment – New Zealand Cape Town Vessels and Foreign Cape Town Vessels (Part 404).

**Maritime New Zealand Consolidated Version
11 April 2024**

This Maritime Transport Instrument is not yet in force. Several things must happen before it is in force.

The Cape Town Agreement must reach the threshold number of States and vessels. When it has, then the Agreement will enter into force after a transition period of 1 year.

This maritime transport instrument comes into force on the same date that Part 404 comes into force. The entry into force of Rule Part 404 will be at the same time as the Agreement comes into force and be notified in the NZ Gazette soon after the Agreement has reached its threshold.

ISBN 978-1-99-001670-7

Published by:

Maritime New Zealand, PO Box 25620, Wellington 6146, New Zealand

Maritime New Zealand Copyright 2024

Disclaimer:

This document is the current consolidated version of Maritime Transport Instrument MTI 404.181-1 produced by Maritime New Zealand, and serves as a reference only. It has been compiled from the official Maritime Transport Instrument that has been signed into law by the Director of Maritime New Zealand. Copies of the official Maritime Transport Instrument and amendments as signed by the Director of Maritime New Zealand may be downloaded from the Maritime New Zealand website. www.maritimenz.govt.nz

History of MTI 404.181-1

Entry into Force

This maritime transport instrument comes into force on the same date that Part 404 comes into force.

Part 404 comes into force on a date applied, either wholly or in part, by notice in the Gazette under section 451(3) of the Maritime Transport Act 1994.

The Part 404 Rules (Part 404) will implement the requirements of the Cape Town Agreement of 2012 (the Agreement) into New Zealand domestic law.

The Agreement will enter into force 12 months after at least 22 States, with a total number of 3,600 fishing vessels of 24 metres in length and over operating on the high seas have acceded. As at this date the entry into force criteria have yet to be met.

Amendment	Effective date
No amendment	Not applicable

Summary of amendments

No amendments

All signed rules can be found on our website:

<https://www.maritimenz.govt.nz/Rules/>

Section 1 Preliminary provisions

1.1 Title

This maritime transport instrument is the *Maritime Transport (Bulwarks, rails, and guards) Instrument* (also referred to as MTI-404.181-1).

1.2 Commencement

This maritime transport instrument comes into force on the same date that Part 404 comes into force.

1.3 What this maritime transport instrument does

This maritime transport instrument (MTI-404.181-1) sets out further requirements in relation to the standards for bulwarks, rails, and guards on vessels.

1.4 Conflicts

- (1) If there is a conflict between a provision in this maritime transport instrument and a corresponding provision of a maritime rule, the provision of the maritime rule applies.
- (2) If there is a conflict between a provision in this maritime transport instrument and a corresponding provision of material incorporated by reference in this maritime transport instrument, the provision of this maritime transport instrument applies.

Section 2 Definitions

2.1 Definitions

All terms used in this maritime transport instrument and defined in Part 404 but not defined in this maritime transport instrument have the same meaning as set out in Part 404.

Section 3 Application

3.1 Application of maritime transport instrument MTI-404.181-1

This maritime transport instrument applies as follows:

- (1) Section 5 applies to vessels to which rule 404.181(1) applies.
- (2) Section 6 applies to vessels to which rule 404.181(2A) applies:

Section 4 Incorporation by reference

4.1 Materials incorporated by reference in this instrument

- (1) the Agreement

Section 5 Alternatives for bulwarks, rails, or guards

- (1) If a bulwark or guardrail will impede the safe navigation of a particular vessel, other means of protecting the safety of the crew may be used on that vessel if that means is acceptable to the Director.

Section 6 Bulwarks, rails, and guards

Compliance either with option 1 or option 2 is required.

Option 1: compliance with the standards for bulwarks, rails, and guards verified by a classification society named in rule 404.30(2)(a):

Option 2: compliance with the standards set out below.

Method of calculation of the minimum distance from the deepest operating waterline to the lowest point of the top of the bulwark or to the edge of the working deck (regulation VI/3)

- (1) The minimum vertical distance from the deepest operating waterline to the lowest point of the top of the bulwark or to the edge of the working deck if guard rails are fitted, referred to in regulation VI/3, should be determined for each vessel, taking into account the probability of shipping water on the deck when the vessel is in moderate beam seas when fishing. This probability should not be greater than 5 percent. The calculations should take account of the damping coefficient associated with the presence of bilge keels or any other roll damping arrangements.
- (2) Where no national practice exists, this distance may be determined by means of the following formulae, based upon the regression analysis of results of the calculations of the probability of shipping water on deck, which is assumed to be 5 percent when the vessel is fishing in beam seas with the significant wave heights of about 2.9 m and about 1.4 m respectively:

$$H = 0.53 + 0.11B + 0.32 (2.60 - B/d) + 0.85 (CB - 0.60) + 0.61 (GM - 0.70) \text{ metres}$$

for vessels that are intended to stop their fishing operations at the significant wave heights of more than 2.9 m, and

$$H = 0.80 + 0.23 (2.60 - B/d) + 0.52 (CB - 0.60) + 0.62 (GM - 0.70) \text{ metres}$$

for vessels that are intended to stop their fishing operations at the significant wave heights of 1.4 m.

If the significant wave heights are between 2.9 m and 1.4 m, the values of H should be determined by linear interpolation. In the above formulae:

B = maximum breadth of the vessel, measured amidships to the moulded line of the frame in a vessel with a metal shell and to the outer surface of the hull in a vessel with a shell of any other material (metres)

d = maximum permissible moulded draught (metres)

CB= block coefficient

GM = initial metacentric height (metres)

All dimensions correspond to the deepest operating waterline.